

# KM-C2525E SPECIFICATIONS

## BASIC SPECIFICATIONS:

Configuration:	Workgroup Color Multifunctional with Standard Network Print / Scan and Optional Fax / Network Fax. Standard Duplex, 500 x 2 Sheet Paper Drawers and 100 Sheet Multipurpose Tray. Standard 40GB System Hard Disk Drive. Optional Document Processor, Paper Handling and Advanced Finishing.
Resolution:	Multi-Bit 600 x 600 DPI Resolution / 256 Levels
System Memory:	Standard 768MB RAM; 40GB HDD
Magnification:	Full Size, 5 Reduction, 5 Enlargement Preset Ratios, Plus 25-400% Zoom (at 1% increments)
Electrical Requirements:	120V, 60Hz, 12A
Dimensions:	23.82"W x 25.98"D x 29.33"H
Weight:	216 lbs
Max Monthly Volume:	85,000 Pages Per Month

## OUTPUT SPEEDS:

Warm-Up Time:	Within 45 Seconds, Program During Warmup, Auto Start
First Copy Out (Color / Mono):	7.9/5.9 Seconds
First Print Out (Color / Mono):	7.9/5.9 Seconds
Pages Per Minute (Color / Mono):	25/25 Letter, 13/13 Legal and Ledger

## PAPER SUPPLY:

Standard Paper Sources:	Dual 500 Sheet Drawers, 100 Sheet MPT, Auto Selection / Switching, Add Paper While Running
Drawer Paper Size:	5.5" x 8.5" - 11" x 17"
MPT Paper Size :	5.5" x 8.5" - 11" x 17"
Std / Max Paper Capacity:	1,100 / 4,100
Paper Weight:	16 - 28 lb Bond via Paper Drawers, 16 lb Bond - 120 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Cardstock, Envelopes

## DUPLEX UNIT:

Paper Size:	5.5" x 8.5" - 11" x 17"
Paper Weight:	16 - 28 lb Bond
Duplex Modes:	Standard 1:2, 2:2, Book: 2, 2:1

## COPY FUNCTIONS:

Imaging Modes:	Text, Photo, Text / Photo, Auto, Manual, ECO, Map
Continuous Copy:	Up to 999, Auto Reset to 1
Additional Features:	Positive / Negative Reverse, Mirror Image, Rotate Copy, Border Erase, Split Copy, Rotate Sort, Full-Color & Monochrome copy sets in same run, Electronic Sort, Margin Shift, XY Zoom
Job Management:	Job Interrupt, Job Build, 8 Job Programs, Repeat Copy, 1,000 Department Management Codes
Color Adjustment:	OneTouch, Color Balance, Hue, Auto Exposure, 6 Monotone Colors, Manual Exposure, Auto GrayScale, Sharpness, Color Calibration

## PAPER HANDLING OPTIONS:

### DOCUMENT PROCESSOR: DP-710

Type:	Reversing Automatic Document Processor
Acceptable Originals:	5.5" x 8.5" - 11" x 17", Mixed Size Originals
Capacity:	100 Sheet RADF / 32 Letter Size Originals Per Minute
Paper Weight:	9 - 42 lb Bond
Dimensions / Weight:	22.5"W x 19.2"D x 5.28"H / 25.4 lbs

### FINISHER: DF-710

Stack Capacity:	Main Tray: 3,000 Sheets; Sub Tray (B): 200 Sheets; Sub Tray (C): 50 Sheets
Paper Size:	Main Tray: 8.5" x 11" - 11" x 17"; Sub Tray (B): 5.5" x 8.5" - 11" x 17"; Sub Tray (C): 8.5" x 11"
Paper Weight:	16 - 28 lb Bond
Staple Capacity:	50 Sheets: 8.5" x 11"; 30 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position:	3 Positions: Top Left, Bottom Left, Center Bind
Punch:	Optional 2 and 3 Hole
Saddle Stitch / Fold:	Optional Booklet Folder
Dimensions / Weight:	26.9"W x 22.2"D x 42.8"H / 125.6 lbs

### SIMPLE FINISHER: DF-730

Stack Capacity:	1,000 Sheets
Paper Size:	8.5" x 11" - 11" x 17"
Paper Weight:	16 - 28 lb Bond
Staple Capacity:	30 Sheets: 8.5" x 11"; 20 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position:	1 Position: Top Left
Dimensions / Weight:	21.9"W x 20.7"D x 36.1"H / 55 lbs

### BOOKLET FOLDER UNIT: BF-710

Folding Capacity:	Up to 16 Sheets
Capacity:	1 - 3 Sheets - 30 Booklets; 4 - 6 Sheets - 20 Booklets; 7 - 16 Sheets - 10 Booklets
Paper Size:	8.5" x 11", 11" x 17", 8.5" x 14"
Paper Weight:	16 - 28 lb Bond, Over 20 lb is one sheet only
Dimensions / Weight:	25.7"W x 17.9"D x 10.5"H / 46.3 lbs

## JOB SEPARATOR: JS-710

Stack Capacity:	100 Sheets
Paper Size:	8.5" x 11" - 11" x 17"
Paper Weight:	16 - 28 lb Bond

## MULTI-BIN MAILBOX: MT-710

Number of Trays:	7
Tray Capacity:	100 Sheets: 5.5" x 8.5", 8.5" x 11"; 50 Sheets: 8.5" x 14", 11" x 17"
Paper Weight:	16 - 20 lb Bond
Dimensions / Weight:	20.0"W x 15.7"D x 18.5"H / 22 lbs

## PUNCH UNIT: PH-5A

Paper Size:	8.5" x 11" - 11" x 17"
Paper Weight:	16 - 28 lb Bond
Number of Holes:	2 and 3
Weight:	6.6 lbs

## LARGE CAPACITY TRAY: PF-750

Paper Capacity:	3,000 Sheets
Paper Weight:	16 - 28 lb Bond
Paper Size:	8.5" x 11"
Dimensions / Weight:	23.0"W x 23.6"D x 12.4"H / 50.7 lbs

## DUAL PAPER DRAWERS: PF-710

Paper Capacity:	500 Sheets x 2
Paper Weight:	16 - 28 lb Bond
Paper Size:	5.5" x 8.5" - 11" x 17"
Dimensions / Weight:	23.0"W x 23.2"D x 12.4"H / 57.3 lbs

## STANDARD PRINT/SCAN:

### PRINT:

Controller:	Embedded PowerPC750fL / 600 MHz Controller
Printer Memory:	Standard 256MB, Upgradeable to 1GB via 100 Pin DIMMS, Optional Printer HDD, Standard CF Card Slot (Type 1)
Supported PDL/Emulations:	PRESCRIBE, PCL6 (PCL XL,PCL 5c), KPDL3 (PS3), KCGL (HP-GL/2)
Fonts:	80 Outline Fonts for PCL XL/5c, 136 Outline Fonts for KPDL3, 1 Bitmap Font
Windows® OS Compatibility:	Windows 95/98/Me/NT4.x/2000/XP/2003/Vista
Novell® OS Compatibility:	Novell NetWare 3.x/4.x/5.x/6.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Standard Interface:	10/100BaseTX, Parallel IEEE1284, High Speed USB 2.0
KUIO LV Expansion Slots (2):	Optional 40GB Printer Hard Disk Drive Optional IB-23 Secure NIC
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows 64-Bit Drivers
Utilities:	KMnet Admin, KM-NET Viewer, KM-NET for Client, KX SpoolCenter, PDF Direct Print, PRESCRIBE Utilities
Web Interface:	Kyocera Command Center

### SCAN:

Type:	Color and Monochrome Scanner
Resolution:	200, 300, 400, 600 DPI
Scan Speed (Color / Mono):	Up to 32 / 32 Sheets Per Minute
File Formats (Color / Mono):	PDF, JPEG / PDF, TIFF
Enhanced PDF Scanning:	PDF Encryption, PDF Compression
Connectivity:	10/100BaseTX
Supported Protocols:	TCP/IP
Scanning Features:	KM Document Flow (Scan to Database) TWAIN (PC/Mac) Scan to File (PC/Mac), Scan to FTP, Scan to e-Mail
Driver:	TWAIN Driver
Utilities:	KM DB-Assistant, KM Scanner File Utility, KM Scanner Address Book, Address Book Editor, LDAP Converter Utility, Network Advanced Setup Utilities, Scan to Mac Utility

### OPTIONAL DATA SECURITY KIT: (D)

Provides Security Overwrite and Encryption for Print, Copy, and Scan

### OPTIONAL FAX/NETWORK FAX: FAX SYSTEM (N)

Compatibility:	Super G3
Transmission Speed:	Approximately 3 Seconds per page
Modem Speed:	33.6 Kbps with Auto Fallback
Data Compression:	JBIG, MMR, MR, MH
Fax Memory (Std/Max):	4MB / 32MB
Driver:	KM Network Fax Driver
Utilities:	Address Book for Network Fax, Address Editor for Fax
Additional Features:	Duplex TX/RX, Confidential RX/TX, Polling, Broadcasting, 2 in 1 RX

### ADDITIONAL OPTIONS:

KYOcapture, KYOcapture Express, iTag, 32MB Fax Memory (MM13-32), Platen Cover, Attachment Kit (AK-710), Printer Memory 128, 256, 512 MB RAM, Printer Hard Disk Drive, Stand



Specifications and design are subject to change without notice. For the latest on connectivity visit [www.kyoceramita.com](http://www.kyoceramita.com). All trademarks are the property of their respective owners.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA  
©2007 Kyocera Mita America, Inc.  
Item Code# 855D400088



[www.kyoceramita.com](http://www.kyoceramita.com)