FS-1030D Specifications

BASIC SPECIFICATIONS:

| Configuration: | Desktop Monochrome Printer with Standard 250 Sheet Drawer plus 50 Sheet Multi-Purpose Tray and Duplex Unit |
|--------------------------|---|
| Resolution: | Fast 1200 mode (1800 x 600 dpi), 600 x 600 dpi, 2400 x 600 dpi (w/KIR) |
| Printer Memory: | Standard 32MB, upgradable to 288MB via 100 pin DIMMs; Standard CF Card Slot (Type 1) |
| Electrical Requirements: | 120V, 60Hz, 7.1A |
| Dimensions: | 14.9"W x 14.8"D x 9.3"H |
| Weight: | 23.2 lbs |
| Max Duty Cycle: | 25,000 Pages |
| max buty oyotot | Editor I agos |

CONTROLLER SPECIFICATIONS:

| Controller: | PowerPC405 266 MHz |
|------------------------------|--|
| Supported PDL / Emulations: | PRESCRIBE, PCL6 (PCL XL, PCL5e), KPDL3 (PS3), Diablo 630, |
| | IBM ProPrinter X24E, Epson LQ850, Line Printer |
| Fonts: | 80 Fonts for PCL XL/5e and KPDL3, 1 Bitmap Font |
| Windows OS Compatibility: | Windows 95/98/Me/NT4.x/2000/XP |
| Novell OS Compatibility: | Novell Netware 3.x/4.x/5.x/6.x |
| Mac OS Compatibility: | OS 8.x/9.x/10.x |
| UNIX OS Compatibility: | Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR) |
| Connectivity / Interface: | Standard IEEE 1284 Parallel, Full-Speed USB 2.0. |
| KUIO LV Expansion Slots (1): | Optional IB-11 Serial Interface; IB-21E 10/100BaseTX Network |
| | Interface |
| Supported Protocol: | TCP/IP, IPX/SPX, AppleTalk, NetBEUI |
| Driver: | KX Driver for Windows , PPD for Mac, PPD for Linux/UNIX |
| Utilities: | KM-NET Viewer, KM-NET for Clients, |
| | Network Advanced Setup Utilities, PRESCRIBE Utilities |
| | |

| OUTPUT SPEEDS: | |
|-------------------------|--|
| Warm-Up Time: | Less than 10 Seconds |
| First Print Out: | Less than 15 Seconds |
| Pages Per Minute: | 23 Letter, 12 ipm Duplex |
| PAPER SUPPLY: | |
| Standard Paper Sources: | 250 Sheet Drawer, 50 Sheet MPT |
| Drawer Paper Size: | 8.5" x 11", 8.5" x 14", A4, B5, A5 |
| MPT Paper Size: | 8.5" x 11", 8.5" x 14", A4, B5, A5, |
| | Custom (2.8" x 5.8" - 8.5" x 14") |
| Std/Max Paper Capacity: | 300 Sheets/550 Sheets |
| Paper Weight: | 16-28 lb Bond via Paper Drawer, 16 lb Bond - 90 lb Index via MPT |
| Input Materials: | Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes |
| | |
| DUPLEX UNIT | |
| Paper Size: | 8.5" x 11", 8.5 x 14 , A4 |
| Paper Weight: | 16 - 28 lb Bond |

PAPER HANDLING OPTIONS:

PAPER DRAWER: **PF-17**

| Paper Capacity: | 250 Sheets |
|----------------------|------------------------------------|
| Max. Drawers: | 1 |
| Paper Weight: | 16 - 28 lb Bond |
| Paper Size: | 8.5" x 11", 8.5" x 14", A4, B5, A5 |
| Dimensions / Weight: | 14.9"W x 14.7"D x 3.1"H/4.8 lbs |

CONSUMABLES:

| TK-122: | 7,200 pages @ 5% Coverage |
|---------|---|
| | * Ships with 3,600 pages @ 5% Coverage. ISO 19752 Certified |



Document Solutions marks are the property of their respective manufacturers.

Kyocera Mita America, Inc. 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA '2005 Kyocera Mita America, Inc. www.kyoceramita.com



Ecosys.